

TECHNICAL DATA SHEET



G4 BAG FILTER

Description

Environmentally safe shatter-proof synthetic fibre welded pockets giving high self-rigidity, 20mm or 25mm galvanized steel header frame (25mm also available in plastic)

Suggested Applications

For use in general air conditioning situations and as pre-filtration for fine filters and paint shops

Technical Data

(based on nominal 24 x 24 x 15 6 pocket size)

Filter Media Type	Synthetic
Av Efficiency @ 5 Micron	>95 %
Nominal Air Volume	3400 m ³ /h
Initial Pressure Drop @ Rated Flow	40 Pa
Final Pressure Drop	250 Pa
Filter Classification EN779:2012	G4 Grade
Filter Classification ISO 16890	Coarse 60%
Temperature Resistance	>80 °C
Maximum Humidity	>100 %
Flammability (DIN53438-3)	F1 Class

☐ Head Office:

39 Moorbridge Road Industrial Estate
Bingham, Notts NG13 8GG
tel: 01949-485400
fax: 01949-485401
email: sales@midfilters.co.uk

☐ Scottish Branch:

28-30 Carron Place
East Kilbride G75 0YL
tel: 01355-267730
fax: 01355-267811
email: scotland@midfilters.co.uk

VAT Registered No. 416 3203 90
Registered in England No. 1936235

